

Dual Mode Wireless Function

DG-BG4100NU has a built in Access Point which allows multiple wireless clients to access the LAN resources and Internet wirelessly. The router also supports configuration of 4 additional Guest wireless networks with user isolation. The router can bridge wirelessly to another Access Point to extend the wireless network by few meters.

Robust WLAN Security (WPA, WPA 2 – PSK)

DG-BG4100NU supports robust security using WPA2 which enhances the security of wireless network to protect sensitive data from hackers. DG-BG4100NU also supports 64/128 bit WEP encryption which offers first level of security choice to home users to provide confidentiality of the wireless network.

Quick & Easy Secure Wireless Setup

The DG-BG4100NU wireless broadband router supports WPS (Wi-Fi Protected Setup), which simplifies wireless client setup procedures (using push button). This enables user to secure their wireless network quickly and easily.

Quality Of Service (QoS)

This router supports Quality of Service based on the application, IP address and the physical port based users. The priority can be set in 4 different levels i.e. highest, high, normal and low depending on the type of traffic. The 4 LAN ports of the router can also be assigned priority depending on the type of traffic they carry.

3G/ ADSL Failover

The DG-BG4100NU provides redundancy by switching Internet connection between ADSL Port and 3G to provide redundancy in case Primary WAN link fails. This ensures uninterrupted Internet services to users.

150 Mbps Wireless ADSL 2/2+ Broadband Router with USB Port

DG-BG4100NU

DIGISOL Wireless broadband router DG-BG4100NU is high-performance ADSL router providing downstream speed of up to 24Mbps and upstream speed upto 1Mbps. It provides one RJ11 telephone Port for ADSL connection, four RJ45 Ethernet interfaces for connecting to notebook/desktop computer or other network devices, One USB 2.0 Port for connecting popular 3G Datacards & Mass Storage.

DIGISOL DG-BG4100NU has Web-based graphic user interface (GUI), which allows user to easily configure the settings and connect to ISP. It also provides detailed information like flow statistics, connection status, etc.



Technical Specifications

Hardware Interfaces:

- One RJ-11 port (for ADSL Line)
- Four 10/100Mbps RJ-45 Ports.
- One Power switch
- One Reset button
- One Wireless antenna
- One WLAN/WPS button
- One USB 2.0(Host) Port

Product Features & Compliances:

- Full rate ADSL 2/2+ Router, Provides 24Mbps downstream & 1Mbps upstream
- UPTO 150Mbps Wireless Speed
- IPv6 Ready
- 3G Backup Support for Internet
- USB Mass Storage Support
- WPS Push Button
- Best for Small & Home Office

ADSL Standards:

- RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5,
- RFC1483, PPPoE, RFC1662 PPP in HDLC-like Framing, MER, G.992.1 (T1.413) ,
- G.992.2 (G.dmt), G.lite G.992.3 (G.bis/ADS L2), G.992.5 (ADSL2+)
- Annex L (reach extended ADSL2), ATM forum UNI3.0, 3.1 and 4.0 permanent virtual circuits (PVCs), CBR, UBR, VBR-rt and VBR-nrt , ITU-T i.610F4/F5 OAM

Standards compliance:

- IEEE 802.3, IEEE 802.3u, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, UDP, IP, ICMP, TCP, ARP, DHCP, SMTP, IPv4 and IPv6, SNMP

Wireless frequency:

- 2.400~2.4835GHz

Wireless output power:

- IEEE802.11b: 16+- 1.5dbm,
- IEEE802.11g: 15+- 1.5dbm,
- IEEE802.11n: 14+- 1.5dbm

Wireless security:

- WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES), WPA/WPA2 Mixed Mode, WPS (PBC/PIN Mechanism), Disable SSID broadcast, IEEE802.1x RADIUS

WLAN data transfer rates:

- IEEE802.11b: 11Mbps, IEEE802.11g: 54Mbps, IEEE802.11n: 150Mbps

Advanced features:

- Port forwarding (Virtual Server), Port triggering, VPN Pass through, DMZ, QoS, UPnP
- DDNS, SNMP, Wireless Bridge function, Guest wireless network (up to 4)
- Static Routing, NAT IP Mapping, USB Mass Storage support, 3G Support

Advanced firewall features:

- Wireless access control (MAC Address based), URL/Keyword Filtering, NAT support IP Filter, Anti DOS protection, ALG

Routing:

- Static routing, Dynamic routing (RIP v1 and v2)

Management features:

- Web GUI interface (HTTP), Backup and Restore Configuration, Remote management
- Quick Setup Utility, TR0-69

Status LEDs:

- Power, WLAN, DSL, Internet, WPS, LAN ports 1~4,USB

Environmental specifications:

- Operating temperature: 0°C ~ 40°C, Storage temperature: -20°C ~ 70°C
- Operating humidity: 10 ~ 95% (Non-condensing), Storage humidity: 5 ~ 95% (Non-condensing)

Power Supply:

- AC power adaptor: 100VAC-240VAC
- DC voltage: 12V, 1A

Dimensions:

- Net Dimensions (L x W x H): 166 x 124 x 29 mm
- Gross Dimensions (L x W x H): 243 x 168 x 70 mm

Weights:

- Net Weight: 244 g
- Gross Weight: 534 g

Package Contents:

- DG-BG4100NU ADSL2/2+ Wireless Broadband Router
- Quick Installation Guide
- Installation Guide CD
- Switching Power Adapter
- POTS Splitter
- Two RJ11 cables
- One RJ45 patch cord

Warranty:

- Lifetime

Minimum System requirements:

- Notebook or Desktop PC
- With Ethernet Network adapter (Wired/WLAN)
- Windows 2000/ WinXP/ Vista/Win 7
- Web browser
- AC Power Socket (100V~240V, 50/60Hz)



Ordering Information:

DG-BG4100NU: DIGISOL 150 Mbps Wireless ADSL 2/2+ Broadband Router with USB Port

DIGISOL, the DIGISOL Logo are trademarks and/or registered trademarks of Smartlink Network Systems Ltd. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2012 Smartlink Network Systems Ltd. All rights reserved.

