

**Technical Specifications**

**Hardware Specifications**

- Ethernet  
1 x 10/100Mbps 802.3af PoE Port
- Antenna: 4dBi
- Design: Ceiling Mount

**Standards Compliance**

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- IEEE 802.3af PoE
- IEEE 802.11b
- IEEE 802.11g
- IEEE 802.11n
- IEEE 802.1x RADIUS Authentication

**WLAN Data Transfer Rates**

- IEEE 802.11b up to 11Mbps
- IEEE 802.11g up to 54Mbps
- IEEE 802.11n up to 300Mbps

**Wireless Functions**

- 802.1q Tag based VLAN Support
- Wifi Operational Modes
  - AP Only Mode
  - WDS Only Mode
  - WDS Hybrid Mode
  - Universal Repeater Mode
- Multiple SSID Support (Upto 8 SSIDs)
- Wireless Security
  - WEP
  - WPA
  - WPA-PSK
  - WPA2
  - WPA2-PSK
  - 802.1x

**Advanced Features**

- Firewall
  - MAC Address Control
- Management
  - UPnP
  - SNMP (v1, v2c, v3)

**Management**

- PC based s/w Platform for Management
- Bulk Firmware Upgrade
- Batch Configuration Upload/ Download
- AP Locking Mechanism for Admin Security
- User Traffic Graphic Analysis using Utility
- Remote AP Management
- WEC Button for Ease of Configuration (MASTER/ SLAVE)
- Backup & Restore Settings
- Web Log, Sys Log & Email Alert Support

**Wi-Fi Transmit Power**

- Up to 26dBm

**Power**

- PoE OR DC 12V/1A

**300Mbps Ceiling Mount Wireless Access Point**

**DG-WM2003SI**



**DIGISOL** Wireless Access Point DG-WM2003SI enables communication between wireless and wired notebooks/desktop computers in the network. It complies with IEEE 802.11n standard and is backward compatible with IEEE 802.11b/g standard. The DG-WM2003SI wireless Access Point can provide wireless data transmission rate up to 300Mbps which enhances the sharing of files, photo, audio, video and gaming experience over wireless network. DG-WM2003SI supports PoE, which helps in easy installation by eliminating the need of a dedicated power source for the camera.

Easy configuration of Master & Slave Access Points with just a press of WEC Button.

**Product Features & Compliances:**

- IEEE 802.11n 2.4GHz Wireless
- 1x 10/100Mbps IEEE 802.3af PoE Port
- Easy Configuration with WEC Button
- Multiple SSID: Up to 8 SSIDs
- IEEE 802.1q Tag based VLAN
- QoS-WMM Support
- Multiple Operational Modes



**Ordering Information:**

**DG-WM2003SI: 300Mbps Ceiling Mount Wireless Access Point**

DIGISOL, the DIGISOL Logo are trademarks and/or registered trademarks of Smartlink Network Systems Ltd. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2012 Smartlink Network Systems Ltd. All rights reserved.